

CERTIFICATE OF APPROVAL

N° 190191

The packaging of type 3H1 plastic jerrican ref. STIHL with a nominal capacity of 5l (310 g ± 5%) manufactured by **EXTRUPLAST – LA ROCHELLE (F) (ref in UN-mark: 2025)** and described in report n° **G-18.365 and G-19.008** issued by IBE-BVI is accepted for the transport by land (road and rail), by sea and by air of dangerous goods mentioned in following annex, within the limits prescribed in that annex.

Type-series packagings shall in every way be in conformity with the approved design type described in the above mentioned report and successfully pass all the tests specified in:

- the IMDG-Code, Part 6
- the European ADR-Agreement, Part 6
- the International RID-Regulation, Part 6
- the ICAO Technical Instructions, Part 6

These packagings shall bear the following mark:



3H1/Y1.0/100/*
B/2025-190191

The mark shall be indelible and preferably inscribed on one of the lateral sides of the packaging. The affixing of the mark shall not weaken the strength of the packaging.

- (*) The two last digits of the year of manufacturing.
Packagings of types 1H and 3H shall also be appropriately marked with the month of manufacturing. This may be marked on the packaging in a different place from the remainder of the mark.

The closing devices of the approved packagings shall be in accordance with those described in the report and bear the following mark: **see Annex IV**

If the closing devices are manufactured by subcontractors, the manufacturer to whom the certificate of approval was assigned remains directly responsible for the conformity of the whole packaging.

Any alteration of the above mentioned packaging (including the closing devices) or of its operating conditions implies the automatic cancellation of this certificate.

The Competent Authorities reserves at any time the right to withdraw this certificate.

Special requirements:

Tests effectuated with the standard liquids :

- Mixture of hydrocarbons

Annex: 4 pages

Brussels, 01/07/2019.




Ing. Maxence Wittebolle,
General Manager
Belgium Packaging Institute

Owner certificate: **(ref in UN-mark: 2025)**

EXTRUPLAST
ZI FIEF DU PASSAGE
AVENUE DE LA REPENTIE
F - 17000 LA ROCHELLE

190191

CERTIFICATE OF APPROVAL N° 190191
ANNEX I TO THE UN CERTIFICATE OF APPROVAL: ROAD AND RAIL TRANSPORT
UN mark


Substances accepted for carriage and conditions for packing
Substances of the classes 1,3, 4.1, 4.2, 4.3, 5.1, 5.2, 6.1, 8 and 9

if allowed by the following sections of the ADR/RID and under the conditions specified in these sections:

3.2, 4.1.4 and 4.1.10 (ADR).

3.2, 4.1.4 and 4.1.10 (RID)

Substances are allowed if they are assimilated to a standard liquid - see section mark 6.1.6.2 .

Water		
1	2	3

Wetting solution		
1	2	3

Acetic acid 98-100 %		
1	2	3


N-butyl acetate		
1	2	3

Mixture of hydrocarbons		
1	2	3
II	1.0	114
III	1.0	114

Nitric acid 55%		
1	2	3

1 = packing group; 2 = max. relative density; 3 = max. vapour pressure at 50° C (kPa)



CERTIFICATE OF APPROVAL N° 190191**ANNEX II TO THE CERTIFICATE OF APPROVAL: SEA TRANSPORT**UN markGeneral conditions

- This packaging may only be used for the dangerous goods for which this packaging is allowed in the IMDG-code and under the conditions specified in that code.
- The dangerous goods may not attack the packaging (nor the closing devices).
- For substances and articles of class 1, the packaging shall also be approved by

FPS ECONOMY

Direction générale Qualité et Sécurité / Algemene Directie Kwaliteit en Veiligheid
Service Réglementation Sécurité / Dienst Reglementering Veiligheid
North Gate III
Boulevard du Roi Albert II, 16
1000 - BRUSSELS

- The manufacturer must inform the user of the packaging and all persons, responsible for the loading and the stowing of the ship, of the conditions specified in this certificate.
- All accidents or events that may influence the security adversely during loading, during the voyage or during the unloading of the ship, shall be reported to

FPS Mobility and Transport

Directorate General Shipping
Port State Control
Posthoflei 3
2600 Berchem
e-mail : SCAntwerpen@mobiliteit.fgov.be
Tel. +32 478 82 58 09



CERTIFICATE OF APPROVAL N° 190191

ANNEX II TO THE CERTIFICATE OF APPROVAL: SEA TRANSPORT

Permitted products

- The products of which the chemical compatibility is shown by testing with the following testliquid(s) (ADR 6.1.6) :

Testliquid	density	Pressure during Hydr. test	remark
water			
acetic acid 98-100 %			
wetting agent solution			
n-butyl acetate			
solution of hydrocarbons (white spirit)	1.0	114	
nitric acid 55 %			

- The products of which the compatibility is shown by the six months test (IMDG-code, 6.1.5.2.5) or another method recognized by the Maritime Transport, "scheepvaartcontrole".

products : nihil



CERTIFICATE OF APPROVAL N° 190191**ANNEX III TO THE CERTIFICATE OF APPROVAL: AIR TRANSPORT**

UN mark



**3H1/Y1.0/100/*
B/2025-190191**

The type of packaging covered by this certificate of approval may be used for the transport by air under following conditions:

- The type of packaging must be allowed by the appropriate packing instruction as detailed in Part 4 of the Technical Instructions.
- The quantities must never exceed the maximum allowed quantities in table 3-1 of the Technical Instructions.
- For combination packagings, the quantities per inner packaging(s) must also not exceed the quantities permitted by the applicable packing instruction.
- The packaging must comply with the general packing requirements of Part 4 chapter 1 and with the packaging specifications of Part 6 of the Technical Instructions.
- For substances and articles of class 1, the package must also be approved by the:

FPS ECONOMY

Direction générale Qualité et Sécurité / Algemene Directie Kwaliteit en Veiligheid
Service Réglementation Sécurité / Dienst Reglementering Veiligheid
North Gate III
Boulevard du Roi Albert II, 16
1000 - BRUSSELS



Annex IV

UN mark



3H1/Y1.0/100/*
B/2025-190191

Authorised closures: (as described in the reports)

Producer: Baxter
Art. Ref: STIHL COL 37 CAPE
Material: HDPE
Gasket: Nitrile joint
Weight: 15,3 g
Torque: 4 Nm
Drawing: E-014